Klemmbacken-Druckschraube || Clamping jaw pressure screw 19.2xx

TECHNISCHE DATEN:

Aufbau

Druckschraube	Messing CuZn39Pb3, galv. vernickelt
Zugentlastungsschelle	Messing CuZn39Pb3, galv. vernickelt
Schrauben	Edelstahl Art.-Nr. 19.207 - 19.236 mit Kreuzschlitzschraube Art.-Nr. 19.242 - 19.248 mit Schlitzschraube
Anschlussgewinde	Pg

Eigenschaften

- Einzelteil zur Verwendung in Kombination mit anderen Komponenten
- sehr hohe Zugentlastung

Temperaturbereich	-60 °C / +200 °C
Schutzart	abhängig von der Kombination mit anderen Komponenten

TECHNICAL DATA:

Configuration

Pressure screw	Brass CuZn39Pb3, nickel-plated
Strain relief clamp	Brass CuZn39Pb3, nickel-plated
Bolts	Stainless steel Part No. 19.207 - 19.236 with Phillips-recessed-head screw Part No. 19.242 - 19.248 with slotted screw
Connecting thread	Pg

Properties

- single part for use in combination with other components
- increased anchorage

Temperature range	-60 °C / +200 °C
Protection grade	dependent on the combination with other components



Merkmale / Characteristics

A	øC*	L	SW1	H	Di		Art.-Nr. / Part No.
	mm	mm	mm	mm	mm		
Pg 7	5 - 7,5	5,5	16	15	7,5	100	19.207
Pg 9	7 - 10	6	19	16	10	100	19.209
Pg 11	8 - 12	6	22	17,5	12	100	19.211
Pg 13,5	10 - 14	7,5	24	18	14	100	19.213
Pg 16	11 - 17	7,5	27	19	17	50	19.216
Pg 21	12 - 22	8	34	21	22	50	19.221
Pg 29	19 - 30	8	42	22	30	25	19.229
Pg 36	25,5 - 37	9,5	52	25,5	38,5	10	19.236
Pg 42	31 - 43	10	59	26,3	43	5	19.242
Pg 48	35 - 48	11	64	27,3	48	5	19.248

* Klemmbereich der Zugentlastung

* Clamping range of anchorage